




16 TRAY / 28 SQ. FT TRAY AREA COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



Ambient -
195°F Precision
Thermostats



Quiet
Operation



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

16CUDG - BILTONG BUNDLE SPECIFICATIONS

Max Power Usage	1.5 kW	Number of Racks	2
Avg Power Usage	750 W	Number of Butcher Hooks	60
Voltage / Frequency	120V/50-60Hz	Total Tray Area	28 sq. ft
Max Amperage	14A	Total Trays	16
Safety Breaker Required	Single Phase/15A (Standard Household Outlet)	Tray Dimensions	16" x 16"
Temperature Range	70°F - 195°F (1°F increments), plus Ambient Air Mode	Space Between Trays	1 2/5"
Timer	0 - 99hr	Tray Mesh Spacing	5/16" x 5/16"
Independent Zones	1	Machine Weight	66 lbs
Average Noise Level	40 dB (Quiet)	Product Dimensions (W x H x D)	18.5" x 2' 4.75" x 22.75"
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish and PF knobs		