




28 TRAY / 130 SQ. FT TRAY AREA COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



Ambient -
195°F Precision
Thermostats



Quiet
Operation



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

28CUDG - BILTONG BUNDLE SPECIFICATIONS

Max Power Usage	7.5 kW (3.75 kw x 2 Zones)	Number of Racks	4
Avg Power Usage	3.75 kW (1.875 kW x 2 Zones)	Number of Butcher Hooks	240
Voltage / Frequency	220-240V/50-60Hz	Total Tray Area	130 sq. ft
Max Amperage	29A	Total Trays	28
Safety Breaker Required	Single Phase/32A (N6-50P Dedicated Outlet)	Tray Dimensions	20" x 33.5"
Temperature Range	70°F - 195°F (1°F increments), plus Ambient Air Mode	Space Between Trays	2"
Timer	0 - 99hr	Tray Mesh Spacing	1/2" x 1/2"
Independent Zones	2	Machine Weight	262 lbs
Average Noise Level	60 dB	Product Dimensions (W x H x D)	2' 10.5" x 5' 6.5" x 2' 2.5"
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish.		