




32 TRAY VERTICAL / 57 SQ. FT TRAY AREA COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



Ambient -
195°F Precision
Thermostats



Quiet
Operation



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

32V CUDG - BILTONG BUNDLE SPECIFICATIONS

Max Power Usage	3.75 kW (1.875 kW x 2 Zones)	Number of Racks	4
Avg Power Usage	1.875 kW (937.5 W x 2 Zones)	Number of Hooks	120
Voltage / Frequency	220-240V/50-60Hz	Total Tray Area	57 sq. ft
Max Amperage	15A	Total Trays	32
Safety Breaker Required	Single Phase/20A (N6-20P Dedicated Outlet)	Tray Dimensions	16" x 16"
Temperature Range	70°F - 195°F (1°F increments), plus Ambient Air Mode	Space Between Trays	1 2/5"
Timer	0 - 99hr	Tray Mesh Spacing	5/16" x 5/16"
Independent Zones	2	Machine Weight	121 lbs
Average Noise Level	45 dB	Product Dimensions (W x H x D)	18.5" x 4' 6" x 22.75"
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish.		