




60 TRAY / 107 SQ. FT TRAY AREA COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



Ambient -
195°F Precision
Thermostats



Quiet
Operation



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

60CUDG - BILTONG BUNDLE SPECIFICATIONS

Max Power Usage	5.75 kW (1.9 kW x 3 Zones)	Number of Racks	6
Avg Power Usage	2.875 kW (958.3 W x 3 Zones)	Number of Butcher Hooks	180
Voltage / Frequency	220-240V/50-60Hz	Total Tray Area	107 sq. ft
Max Amperage	19.56A	Total Trays	60
Safety Breaker Required	Single Phase/25A (N6-50P Dedicated Outlet)	Tray Dimensions	16" x 16"
Temperature Range	70°F - 195°F (1°F increments), plus Ambient Air Mode	Space Between Trays	1 2/5"
Timer	0 - 99hr	Tray Mesh Spacing	5/16" x 5/16"
Independent Zones	3	Machine Weight	194 lbs
Average Noise Level	55 dB	Product Dimensions (W x H x D)	4' 7.5" x 3' .5" x 22"
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish.		